

PORTABLE CRANES

Capacity 0 to Max Lift Series Model	850 lbs (385 kg) up to 236 ft (71.9 m) First Mate® 5PF5	500 lbs (226 kg) up to 235 ft (71.6 m) Ensign® 5PA5	1,200 lbs (544 kg) up to 281 ft (85.6 m) Ensign® 5PA10	650 lbs (300 kg) up to 287 ft (87.4 m) Commander® 5PT5	1,200 lbs (544 kg) up to 287 ft (87.4 m) Commander® 5PT10	2,000 lbs (907 kg) up to 435 ft (132.5 m) Commander® 5PT20
-------------------------------------	--	--	---	---	--	---

STATIONARY CRANES

Capacity 0 to Max Lift Series Model	2,000 lbs (907 kg) up to 278 ft (84.7 m) Captain® 5FT20	2,800 lbs (1,270 kg) up to 278 ft (84.7 m) Captain® 5FT25	5,500 lbs (2,500 kg) up to 174 ft (53.0 m) Captain® 5FT40	3,000 lbs (1,360 kg) up to 224 ft (68.2 m) Admiral® 5PT30
-------------------------------------	--	--	--	--

HEAVY-DUTY ELECTRIC WINCHES

WS Series

Capacity Range	600 lbs (272 kg)	Up to	26,000 lbs (11,793 kg)
Line Speeds	1 fpm (.3 mpm)		100 + fpm (30 + mpm)
Travel Distance	1 ft (.3 m)		400 + ft (122 + m)
H.P.	1		30 +
4WS Models	1M 3M 6M 9M 16M		26M

HS Series

Capacity Range	1,100 lbs (498 kg)	Up to	56,000 lbs (25,401 kg)
Line Speeds	1 fpm (.3 mpm)		100 + fpm (30 + mpm)
Travel Distance	1 ft (.3 m)		1,500 + ft (457 + m)
H.P.	1		60
4HS Models	6M 11M 16M 26M 40M		56M

HWF Series

Capacity Range	1,000 lbs (453 kg)	Up to	8,000 lbs (3,628 kg)
Line Speeds	1 fpm (.3 mpm)		70 + fpm (21 + mpm)
Travel Distance	1 ft (.3 m)		2,000 + ft (610 + m)
H.P.	1		15 +
4HWF Models	1M 2M 4M 6M		8M

HPF Series

Capacity Range	1,000 lbs (453 kg)	Up to	25,000 lbs (11,339 kg)
Line Speeds	1 fpm (.3 mpm)		600 + fpm (183 + mpm)
Travel Distance	1 ft (.3 m)		10,000 + ft (3,048 + m)
H.P.	1		75 +
4HPF Models	2M 3M 5M 7M 9M 15M 20M		25M


HBP Series

Capacity Range	35,000 lbs (15,875 kg)	Up to	100,000 lbs (45,359 kg)
Line Speeds	1 fpm (.3 mpm)		100 + fpm (30 + mpm)
Travel Distance	1 ft (.3 m)		12,000 + ft (3,658 + m)
H.P.	2		75 +
4HBP Models	35M		100M

AIR WINCHES

Big Red Series

Capacity 0 to	3,600 lbs (1,633 kg)	7,200 lbs (3,265 kg)	7,200 lbs (3,265 kg)	18,000 lbs (8,164 kg)	23,600 lbs (10,704 kg)	37,000 lbs (16,782 kg)
Line Speed	94 fpm (29 mpm)	46 fpm (14 mpm)	114 fpm (34 mpm)	47 fpm (14 mpm)	29 fpm (8.8 mpm)	34 fpm (10.4 mpm)
H.P.	7.1	7.1	18.3	17.8	14.4	27
Model	TA2H	TA2	TA2.5	TA5	TA7	TA10



Mini Series

Capacity 0 to	1,400 lbs (635 kg)	2,700 lbs (1,224 kg)
Line Speed	52 fpm (16 mpm)	67 fpm (20 mpm)
H.P.	1.35	3.5
Model	MTA 1000	MTA 2000



C Series

Capacity 0 to	5,500 lbs (2,494 kg)	11,000 lbs (4,989 kg)	22,000 lbs (9,979 kg)
Line Speed	127 fpm (39 mpm)	55 fpm (17 mpm)	31 fpm (9 mpm)
H.P.	TAC	TAC	TAC
Model	TA2.5C	TASC	TA10C



PORTABLE ELECTRIC WINCHES


Max Capacity	1,000 lbs (453 kg)	2,000 lbs (907 kg)	1,500 lbs (680 kg)	2,000 lbs (907 kg)	4,600 lbs (2,086 kg)
Line Speed	35-50 fpm (11-15 mpm)	19 fpm (5.8 mpm)	97 fpm (29.6 mpm)	22 fpm (6.7 mpm)	24 fpm (7.3 mpm)
H.P.	----	1.3	3	1.5	3
Series	Liberty®	Atlas	Atlas	Dura Hoist	Atlas II
Model	3CPIS-AFS	4WP2T8	4WP2D8	4771	3WG4



HAND WINCHES

Spur Gear

Capacity 0 to	1,000 lbs (453 kg)	2,000 lbs (907 kg)	4,000 lbs (1,814 kg)	10,000 lbs (4,535 kg)
Gear Ratio	3:1	15:1	20:1	25:1
Approx. Weight	17 lbs (7.7 kg)	28 lbs (12.7 kg)	91 lbs (41.3 kg)	173 lbs (78.5 kg)
Model	M4022PB	M4312PB	M452B	M492B



Worm Gear

Capacity 0 to	1,000 lbs (453 kg)	2,000 lbs (907 kg)	4,600 lbs (2,086 kg)
Gear Ratio	15:1	32:1	31:1
Approx. Weight	21 lbs (9.5 kg)	41 lbs (18.6 kg)	123 lbs (55.8 kg)
Model	4622PB	4WM2	2W40



Worldwide Distribution

Thern, Incorporated
 Corporate Headquarters & Manufacturing
 5712 Industrial Park Road, Winona, MN USA
 TF: 1-800-843-7648 P: 1-507-454-2996
 email: info@thern.com
 www.thern.com



Thern Europe
 Bedrijvenpark Twente 454e 7602 KM
 Almelo, Netherlands
 P: +31-546-898-380
 europe@thern.com

LCIN-A-0221

Thern products are not for lifting people or things over people.